

NV10

No VOCs

SCAQMD Rule 1168
Compliant

OTC Compliant

LEED Compliant

Flammable DOT

Postformable

Fast Tack

High Temperature
resistance



nevamar

NV10 is a high performance industrial strength contact adhesive formulated with zero VOCs to comply with CA and OTC state regulations. Water resistant and temperature resistant to over 200°F, NV10 is designed for bonding a wide range of substrates to include decorative laminates and veneers, fiberglass, glass, upholstery, fabrics, foam, auto headliners, cork and particle board.

PRODUCT USAGE

NV10 is designed to be applied to both surfaces about to be joined. Spray an even coat of adhesive with at least 80% to 100% coverage of each surface. Allow to dry 3-5 minutes til tacky. Place the surfaces together and apply pressure evenly across the full bonding surface. For best results: Make sure that the surfaces are dry and free from dirt, grease or oil. Ensure that the adhesives and substrates are at 60°F or higher. If surfaces are porous, a second coat is recommended after the first has dried and become tacky.

STORAGE

After use, do not close the valve. Leave the gun and hose connected to the canister. Recommended to store canister off the floor if temperatures below 60°F.

PHYSICAL PROPERTIES

Appearance:	Liquid, clear or red
Specific Gravity:	.95 + .02
Shear Adhesion:	>100psi and >200°F
Spray Tip:	4001
Spray Pattern:	Pebble Spray
Flammability:	Flammable per ASTM E-681-04
VOC:	No VOC's, No ODS, No HAPS
Shelf Life:	15 months
Freezing:	Not damaged by freezing but return to room temp before use.

PACKAGING

NV10-013C(R)	13 oz Aerosol Can
NV10-008C(R)	8 lbs Disposable Canister
NV10-030C(R)	27 lbs Disposable Canister
NV10-140C(R)	130 lbs Returnable Canister
NV10-280C(R)	270 lbs Returnable Canister
NV10-005C(R)	5 gal Pail
NV10-055C(R)	55 gal Drum

All available in Clear (C) or Red (R)

KEY FEATURES

- No VOCs
- SCAQMD Rule 1168 & OTC Compliant
- LEED Compliant
 - LEED Schools EQ Credit 4.0
 - LEED Core & Shell EQ Credit 4.0
 - LEED ND & CI EQ Credit 4.1
 - LEED EB MR Credit 3.0
- Fast Tack Bond Performance
- High Temperature resistance
- Pebble Spray Pattern

Disclaimer of Warranty: Pionite expressly disclaims all warranties either expressed or implied, including but not limited to merchantability and fitness for particular purpose. User is responsible for determining this product is fit for specific purpose and application method and assumes all risk and liability herewith. Manufacturer liability is limited to replacement of product or reimbursement of purchase cost, at our discretion. This provision relates to all sales and cannot be modified.

Mfd. for: Pionite (855) 497-0700

See MSDS Data Sheet for Proper Handling and Safety Information